

Sonus SBC 5400 Session Border Controller

Designed for communications service providers and large enterprises, the SBC 5400 Session Border Controller is a powerful, compact and purpose-built SBC for the multimedia communications of today and tomorrow. With the ability to scale from 2GB to 10GB of multimedia traffic, the Sonus SBC 5400 provides all of the features you need in an SBC today—robust network security, sophisticated routing and policy management, overload controls, SIP normalization—plus the features you'll need tomorrow, such as IPv4-IPv6 interworking, multi-modal communication, built-in media transcoding, and assured performance and scale under heavy traffic. As a key component of Sonus' award-winning SBC Core platform family, the SBC 5400 meets all of the security, scalability, availability, and management requirements of service providers and large enterprises.



System Capabilities

- Sessions
 - 75,000 simultaneous G.729 sessions
 - 50,000 simultaneous G.711 sessions
 - Up to 40,000 transcoded sessions based on codec
 - Up to 32,000 H.323 sessions
 - RTCP sessions scale 1:1 with RTP sessions
- Call Setup
 - Maximum call setup rate: 700 cps
 - Call latency= 30ms (@ 450 cps, 90% fall into this category)
- Registrations
 - Maximum new registrations/sec: 1,250
 - Maximum refreshes/sec: 5,000
 - Total registered end point support: 600,000; up to 600,000 NAT'd end points
- Encryption
 - Maximum number of TLS sessions: 375,000
 - TLS setup rate: 500/sec
 - IPsec (IKE) setup rate: 150/sec
 - Maximum # SRTP call legs: 150,000

Media Services

- Transcoding G.711, G.726, G.729A/B, G.723, iLBC, G.722, G.722.1, AMR-NB, AMR-WB, EVRC/EVRCO, EVRCB/EVRCBO, Opus
- Wireline, wireless, wideband and clearchannel codec pass through
- G.711 fallback for fax and modem calls
- T.38 version 0 to G.711 interworking (transcoding)
- T.38 version 3 to G.711 interworking (transcoding)

- VAD, Silence Suppression, Dynamic Jitter Buffer, Fax/ Modem Detection, DTMF/Tone Relay/RFC2833/RFC4733 interworking
- NAT/NAPT on media
- Message Session Relay Protocol (MSRP)
- DTMF Trigger Detection and Notification
- Generic audio codec relay
- Tones & Announcements
- Local Ring Back Tone (LRBT) support with centralized PSX Policy Server
- RTP inactivity monitoring
- Supported video codecs: H.264 AVC, H.264 SVC, H.263+; H.263, H.261, VP8
- SIPREC

Redundancy

- 1:1 Redundant Systems for Service Availability
- 1:1 Redundant Management/ Control Ports

Management Capabilities

- Graphical based wizards for ease of configuration
- Secure embedded web-based management GUI
- Sonus CLI
- Centralized support by Sonus Insight EMS
- REST API
- SNMP V2/V3 status and statistics

- Local logging of events, alarms, and traps; Call trace
- Sonus DSI Level 0 support for storing CDRs; RADIUS accounting records
- Live Software Update (LSWU)

Signaling

- Back to Back User Agent (B2BUA)
- SIP, SIP-I/SIP-T, SIP/H.323; Sonus Gateway to Gateway Signaling
- SIP protocol normalization/ protocol repair; SIP message manipulation
- NAT/NAPT on signaling
- Binary floor control protocol (BFCP), Far-end camera control (FECC)

Security

- Session aware firewall; Topology Hiding
- Line rate DoS/ DDoS, and Rogue RTP protection
- Line rate malformed packet protection
- TLS, IPsec (IKEV1) for signaling encryption
- Secure RTP/RTCP for media encryption

Protocol Support

- IPv4, IPv6, IPv4/IPv6 interworking
- SSH; sFTP
- SNMP; NETCONF; NTP
- HTTP/HTTPS

- RTP/RTCP
- UDP, TCP
- DNS, ENUM
- WebRTC

Routing/Policy

- Embedded policy/routing engine
- Centralized support by Sonus; PSX Policy/Route Server using DIAMETER+
- Screening, blocking, routing, presentation, call type filters
- Route prioritization
- Leading digit routing; International routing; URI-based routing
- Digit/parameter manipulation
- E911 support; Priority Call handling

Quality of Service (QoS)

- Bandwidth management
- Call admission control (CAC) per trunk group, per zone
- Per call statistics
- TOS/ COS packet marking

Packet Network Time Source

- Network Time Protocol (NTP) per RFC-1708

Hardware Specifications

Front Panel

- Status Indicators Front Panel LEDs:
 - Power
 - Status
 - Active/Standby
 - Major/Minor Alarm
 - Locator

Rear Panel

- Management Ports:
 - Four 100 Mbps Ethernet RJ-45 ports
- Media Ports:
 - Four 1 Gbps Ethernet fiber or copper via SFP with one of the ports being 10GB capable
- High Availability Ports:
 - Two 1 Gbps Ethernet multimode fiber via SFP
- Single Field Service port with RJ45 connector
- Locator LED
- Single serial craft DB9 port

Memory

- 32 Gbytes

DSP Expansion

- Four modular DSP slots for DSP25 cards

Chassis

- 2U, rack mount
- Inches: 17.5" Wide x 3.5" High x 21" Deep
- Centimeters: 44.5 Wide x 8.8 High x 53.3 Deep
- Optional mounting brackets for 19" or 23" rack

Chassis Mounting Options:

- 19" or 23" Adjustable Brackets

Storage

- 512 Gbytes of Solid State Drive (SSD) storage

AC Power Option

- RMS Input Voltage
- Minimum 90 VAC
- Nominal 100-240 VAC
- Maximum 264 VAC

- RMS Current
- 5.6A
- Input Frequency
- Minimum 47 Hz
- Nominal 50/60 Hz
- Maximum 63 Hz

DC Power Option

- Peak Consumption: 17.3 A

Operating Altitude

- 6,000 Feet
- 1,800 Meters

Heat Dissipation

- Fully-Populated Maximum:
 - 1000 Watts
 - 3410 BTU per Hour
 - Replaceable Filter

Weight Maximum Fully Populated

- 50 lbs. (22.68 kg)

Environmental

- 5 to 40° C Operating -5 to 55° C Short Term
- 5 to 90% Non-Condensing Operating Humidity

Regulatory Compliance

Central Office Standards

- DC Systems - SR-3580 NEBS Level 3
 - GR-1089-CORE
 - GR-63-CORE
- AC Systems - SR-3580 NEBS Level 3
 - GR-1089-CORE
 - GR-63-CORE

Table 1. Estimated Power Consumption (all power measurements taken with fans running high)

Configuration	AC Low Line (W)		AC High Line (W)		DC (W)	
	Amps	Watts	Amps	Watts	Amps	Watts
SBC 5400 - No DSP Cards	5.7	512	2.9	516	12.6	502
SBC 5400 +1 DSP25	6.4	576	3.2	582	14.0	559
SBC 5400 +2 DSP25	7.2	644	3.6	647	14.9	594
SBC 5400 +3 DSP25	7.8	702	3.9	702	17.0	678
SBC 5400 +4 DSP25	8.5	761	4.2	763	17.3	692

About Sonus Networks

Sonus brings intelligence and security to real-time communications. By helping the world embrace the next generation of Cloud-based SIP and 4G/LTE solutions, Sonus enables and secures latency-sensitive, mission-critical traffic for VoIP, video, instant messaging and online collaboration. With Sonus, enterprises can give priority to real-time communications based on smart business rules, while service providers can offer reliable, comprehensive and secure on-demand network services to their customers. With solutions deployed in more than 100 countries and nearly two decades of experience, Sonus offers a complete portfolio of hardware-based and virtualized Session Border Controllers (SBCs), Diameter Signaling Controllers (DSCs), Network-as-a-Service (NaaS) capabilities, policy/routing servers, and media and signaling gateways.

Sonus Networks North American Headquarters

4 Technology Park Drive
Westford, MA 01886
U.S.A.
Tel: +1-855-GO-SONUS

Sonus Networks APAC Headquarters

1 Fullerton Road #02-01
One Fullerton
Singapore 049213
Singapore
Tel: +65-68325589

Sonus Networks EMEA Headquarters

Edison House
Edison Road
Dorcan, Swindon
Wiltshire
SN3 5JX
Tel: +44-14-0378-8114

Sonus Networks CALA Headquarters

Homero No. 1933-902
Col. Los Morales, C.P. 11510
Mexico City, Mexico
Distrito Federal
Mexico Tel: +52-55-1950-3036
Int'l Tel: +1-978-614-8741

To learn more, call Sonus at 855-GO-SONUS
or visit us online at www.sonus.net

Microsoft Partner
Gold Communications

Voice
Unified Communications
Business Productivity Solutions
Midmarket Solution Provider

The content in this document is for informational purposes only and is subject to change by Sonus Networks without notice. While reasonable efforts have been made in the preparation of this publication to assure its accuracy, Sonus Networks assumes no liability resulting from technical or editorial errors or omissions, or for any damages resulting from the use of this information. Unless specifically included in a written agreement with Sonus Networks, Sonus Networks has no obligation to develop or deliver any future release or upgrade, or any feature, enhancement or function.

Copyright © 2015 Sonus Networks, Inc. All rights reserved. Sonus is a registered trademark of Sonus Networks, Inc. All other trademarks, service marks, registered trademarks or registered service marks may be the property of their respective owners.